

(12) UK Patent Application (19) GB (11) 2 367 828 (13) A

(43) Date of A Publication 17.04.2002

(21) Application No 0020965.0

(22) Date of Filing 25.08.2000

(71) Applicant(s)

Reckitt Benckiser (UK) Limited
(Incorporated in the United Kingdom)
67 Alma Road, WINDSOR, Berkshire, SL4 3HD,
United Kingdom

(72) Inventor(s)

Paul John Duffield

(74) Agent and/or Address for Service

Reckitt Benckiser plc
Group Patents Departments, Dansom Lane, HULL,
HU8 7DS, United Kingdom

(51) INT CL⁷

C11D 17/04 // A01N 25/00 , B65D 65/46

(52) UK CL (Edition T)

C5D DDX D107 D110 D111 D121 D153 D166 D167 D168
D173 D181 D182

(56) Documents Cited

GB 2118961 A **EP 0347219 A1**
EP 0155606 A2 **WO 94/14941 A1**
WO 94/04656 A1 **WO 92/17382 A1**
CA 001112534 A **US 4973416 A**

Derwent Abstract No 1997-358496[33] relating to
JP090150476 (Aicello) 10.06.1997

Derwent Abstract No 1999-163453[14] relating to
JP110021594 (Kao) 26.01.1999

(58) Field of Search

UK CL (Edition S) A5E ES EX , B8C CWPT1 CWPT2
CWP3 , C5D D181
INT CL⁷ A01N 25/00 , B65D 65/46 , C11D 17/04
Online: WPI EPODOC PAJ

(54) Abstract Title

Water-soluble containers containing aqueous compositions

(57) Water-soluble containers contain aqueous compositions having a free water content of greater than 3 wt%.

The container is of thermoformed PVA film. The composition may be a dishwashing, water-softening, laundry, disinfectant, antibacterial or antiseptic. By the presence of the water in the composition the container is given a fuller appearance.

IMPROVEMENTS IN OR RELATING TO AQUEOUS COMPOSITIONS

The present invention relates to water-soluble containers containing aqueous compositions.

5

It is known to package chemical compositions which may be of a hazardous or irritant nature in water soluble or water dispersible material such as films. The package can simply be added to water in order to
10 dissolve or disperse the contents of the package into the water.

15

For example, WO 89/12587 discloses a package which comprises an envelope of a water soluble or water dispersible material which comprises a flexible wall and a water-soluble or water-dispersible heat seal. The package may contain an organic liquid comprising, for example, a pesticide, fungicide, insecticide or herbicide.

20

It is also known to package detergents in water-soluble or water-dispersible containers. For example, WO 94/14941 discloses a water-soluble or water-dispersible capsule containing an aqueous dishwasher
25 detergent. The capsule is made of gelatin.

30

CA-A-1,112,534 discloses a packet made of a water-soluble material in film form enclosing within it a paste-form, automatic dishwasher-compatible detergent composition. The water-soluble material may be, for example, poly(vinyl alcohol), polyethylene oxide or methyl cellulose. Example 1 illustrates an embodiment wherein a poly(vinyl alcohol) (PVOH) film is made into a 5cm square packet by heat sealing its edges, and the
35 packet is filled with a composition which contains 8.5 wt.% water.

In fields such as detergents for domestic use, an attractive appearance for an article is extremely

desirable. However, in the prior art such as that described above, a bag is simply formed from a single sheet of water soluble film. The film is folded and three of the edges are heat-sealed to form the bag.

5 The bag is then filled and the remaining edge heat sealed. This produces a rather flat, limp envelope containing the product. Furthermore there may be a lack of uniformity between different bags because of their flexible nature.

10

We have discovered that this type of product is not deemed to be attractive by an average consumer.

15

The present invention seeks to provide a water soluble container containing an aqueous composition, which container has a more attractive appearance. In particular the container should be relatively self-supporting and look full. Ideally the container should have an attractive, rounded three-dimensional appearance.

20

It is known to form water-soluble containers by thermoforming a water-soluble material. For example, WO 92/17382 discloses a package containing an agrochemical such as a pesticide comprising a first sheet of non-planar water-soluble or water-dispersible material and a second sheet of water-soluble or water-dispersible material superposed on the first sheet and sealed to it by a continuous closed water-soluble or water-dispersible seal along a continuous region of the superposed sheets. It is stated to be advantageous to ensure that the package produced is evacuated of air or the contents are under reduced pressure to provide increased resistance to shock.

25

30

35 Furthermore, when the package contains a liquid, the liquid must be an organic liquid which must be reasonably dry and typically contains less than 2 to 3% of water to ensure that it does not attack the water-soluble package and cause leakage.

EP-A-654,418 describes self-standing flexible pouches which may contain, for example, liquid detergent compositions for refilling other containers. In order
5 to avoid folding of the pouch, which can lead to cracking and leakage, the bag is inflated before it is sealed.

In order to improve the strength of packages
10 containing liquids, it is also known to provide the package with residual inflatability. Thus, for example, EP-A-524,721 describes a water-soluble package which contains a liquid, wherein the package is inflatable to a volume which is greater than the
15 initial volume of the package. Thus the package is filled to less than its complete capacity, and the unused capacity may be partially, but not totally, filled with a gas such as air. The unused capacity which does not contain gas provides the residual
20 inflatability.

We have now surprisingly discovered a water-soluble container which contains a liquid composition can be given an attractive three-dimensional appearance by
25 using a thermoforming technique such as that disclosed in WO 92/17382 on a PVOH film and ensuring that the liquid composition has a water content which is greater than that used before. Immediately after the containers are prepared, they have a limp,
30 unattractive appearance. However, after storage for a short while, for example from a few minutes to a few hours, they develop a more attractive three-dimensional appearance, and also appear to look fuller. They can also be said to have a "puffed-up"
35 appearance. Although not bound by this theory, it is believed that the water in the aqueous composition shrinks the PVOH film, which was stretched during the thermoforming process, around the liquid composition to provide the attractive appearance.

The present invention accordingly provides a water-soluble container containing an aqueous composition, wherein:

- 5 a) the container comprises a thermoformed PVOH film; and
- b) the aqueous composition contains greater than 3 wt% free water, based on the weight of the aqueous composition.

10 The present invention also provides the use of a thermoformed PVOH film to package an aqueous composition containing greater than 3 wt% water, based on the weight of the aqueous composition.

15 The present invention further provides a process for producing a container as defined above which comprises:

- a) thermoforming a first PVOH film to produce a pocket;
- 20 b) filling the pocket with the aqueous composition;
- c) placing a second PVOH film on top of the filled pocket; and
- d) sealing the first film and second film
- 25 together.

There is no direct correlation between the actual amount of water present in a composition and the amount of free water as required in the present
30 invention. Free water includes water which is not available to the PVOH film such as water held within a gelled matrix or water of solvation of any components present in the composition.

35 In order to determine the amount of free water present in a composition, a standard loss-on-drying determination test may be carried out. A sample of the composition, usually about 10 g, is weighed, and then maintained at 60°C for 3 hours under a partial

vacuum of 200 mbar (20 kPa). The sample is then re-weighed, and the weight lost determined. In the present invention, the loss on drying must be greater than 3 wt%, preferably greater than 4, 5, 6, 7, 8, 9, 10, 11, or 12 wt%, even more preferably greater than 20 wt% or greater than 30 wt%.

The method of forming the container is similar to the process described in WO 92/17382. A first PVOH film is initially thermoformed to produce a non-planar sheet containing a pocket, such as a recess, which is able to retain the aqueous composition. The pocket is generally bounded by a flange, which is preferably substantially planar. The pocket may have internal barrier layers as described in, for example, WO 93/08095. The pocket is then filled with the aqueous composition, and a second PVOH film is placed on the flange and across the pocket. The second PVOH film may or may not be thermoformed. If the first film contains more than one pocket, the second film may be placed across all of the pockets for convenience. The pocket may be completely filled, or only partly filled, for example to leave an air space of from 2 to 20%, especially from 5 to 10%, of the volume of the container immediately after it is formed. Partial filling may reduce the risk of rupture of the container if it is subjected to shock and reduce the risk of leakage if the container is subjected to high temperatures.

The films are then sealed together, for example by heat sealing across the flange. Other methods of sealing the films together may be used, for example infra-red, radio frequency, ultrasonic, laser, solvent, vibration or spin welding. An adhesive such as an aqueous solution of PVOH may also be used. The seal desirably is also water-soluble.

If more than one container is formed at the same time,

the packaged compositions may then be separated from each other by cutting the flanges. Alternatively, they may be left conjoined and, for example, perforations provided between the individual
5 containers so that they can be easily separated at a later stage, for example by a consumer. If the containers are separated, the flanges may be left in place. However, desirably the flanges are partially removed in order to provide an even more
10 attractive, three-dimensional appearance. Generally the flanges remaining should be as small as possible for aesthetic purposes while bearing in mind that some flange is required to ensure the two films remain adhered to each other. A flange having a width of 1
15 mm to 5 mm is desirable, preferably 1.5 mm to 2.5 mm, most preferably about 2 mm.

The containers may then be left for a while to attain their attractive appearance, or may be immediately
20 packaged into boxes for retail sale, and left to attain their attractive appearance in the boxes. The containers may themselves be packaged in outer containers if desired, for example non-water soluble containers which are removed before the water soluble
25 containers are used.

If more than one PVOH film is used for the containers, the films may be identical or different. The PVOH film may be partially or fully alcoholised or hydrolysed,
30 for example, it may be from 40 to 100%, preferably 70 to 92%, more preferably about 88%, alcoholised or hydrolysed, polyvinyl acetate film. The film may be cast, blown or extruded. It may also be unorientated, mono-axially oriented or bi-axially oriented.

35 The film is generally cold water (20°C) soluble, but, depending on its degree of hydrolysis, may be insoluble in cold water at 20°C and only become soluble in warm water or hot water having a

temperature of, for example, 30°C, 40°C, 50°C or even 60°C. If the film is soluble in cold water, or water at a temperature of up to, say, 35°C steps must be taken to ensure that the aqueous composition contained
5 inside the container does not dissolve the film from the inside. Steps may be taken to treat the inside surface of the film, for example by coating it with an agent such as poly(vinyl dichloride) or PTFE (polytetrafluoroethylene), or to adapt the composition
10 to ensure that it does not dissolve the film. For example, it has been found that ensuring the composition has a high ionic strength or contains an agent which minimises water loss through the walls of the container will prevent the composition from
15 dissolving the PVOH film from the inside. This is described in more detail in EP-A-518,689 and WO 97/27743.

It is particularly important to avoid pinholes in the
20 film through which leakage of the contained composition may occur. It may therefore be appropriate to use a laminate of two or more layers of a different or the same PVOH film, as pinholes are unlikely to coincide in two layers of material.
25 When a first and second PVOH film are used to form the containers of the present invention, the first PVOH film will generally have a thickness before thermoforming of 20 to 500 μm , especially 70 to 400 μm , for example 70 to 300 μm , most preferably 70 to
30 160 μm , especially 75 to 100 μm . The thickness of the second PVOH film may be less than that of the first film as the second film will not generally be thermoformed so localised thinning of the sheet will not occur. The thickness of the second film will
35 generally be from 20 to 160 μm , preferably from 50 to 100 μm .

The films may be chosen, if desired, such that they have the same thickness before the first film is

thermoformed, or have the same thickness after the first sheet has been thermoformed in order to provide a composition which is encapsulated by a substantially constant thickness of film.

5

The containers of the present invention generally contain from 5 to 100 g of aqueous composition, especially from 15 to 40 g, depending on their intended use. For example, a dishwashing composition
10 may weigh from 15 to 20g, a water-softening composition may weigh from 25 to 35g, and a laundry composition may weigh from 30 to 40g.

15

The containers may have any shape achievable by thermoforming. For example they can take the form of a cylinder, cube or cuboid, i.e. a rectangular parallelepiped whose faces are not all equal. In general, because the containers are not rigid, the sides are not planar, but rather are convex. If the
20 container is formed from a thermoformed PVOH film and a planar PVOH film, the seam between the two films will appear nearer one face of the container rather than the other. Apart from the deformation of the container due to the shrinkage of the PVOH film
25 discussed above, deformation may also occur at the stage of manufacture if desired. For example, if the pocket is filled with a gelled composition having a height greater than that of the pocket, the second film will be deformed when placed on top of the
30 pocket.

35

In general the maximum dimension of the filled part of the container (excluding any flanges) is 5 cm. For example, a rounded cuboid container may have a length
of 1 to 5 cm, especially 3.5 to 4.5 cm, a width of 1.5 to 3.5 cm, especially 2 to 3 cm, and a height of 1 to 2 cm, especially 1.25 to 1.75 cm.

The container of the present invention desirably


contains an aqueous composition which is a dishwashing, water-softening, laundry or detergent composition or a rinse aid. In this case the container is preferably suitable for use in a domestic washing machine such as a laundry washing machine or a dishwashing machine. The composition may also be a disinfectant, antibacterial or antiseptic composition intended to be diluted with water before use, or a concentrated refill composition, for example for a trigger-type spray used in domestic situations. Such a composition can simply be added to water already held in the spray container.

The composition contains greater than 3 wt% free water based on the weight of the aqueous composition, in order to ensure that the container has an attractive appearance. However, the actual amount of water present in the composition may be in excess of the amount of free water since the total water content includes water of solvation and water held within a gelled matrix. The total amount of water is generally more than 5 wt%, for example more than 10, 15, 20, 25 or 30 wt%. The total water content may be less than 80 wt%, for example less than 70, 60, 50, 40 wt%. It may, for example, contain from 30 to 65 wt% total water.

The remaining ingredients of the aqueous composition depend on the use of the composition. Thus, for example, the compositions may contain surface active agents such as an anionic, nonionic, cationic, amphoteric or zwitterionic surface active agents or mixtures thereof.

Examples of anionic surfactants are straight-chained or branched alkyl sulfates and alkyl polyalkoxylated sulfates, also known as alkyl ether sulfates. Such surfactants may be produced by the sulfation of higher C₈-C₂₀ fatty alcohols.

Examples of primary alkyl sulfate surfactants are those of formula:




5 wherein R is a linear C₈-C₂₀ hydrocarbyl group and M is a water-solubilising cation. Preferably R is C₁₀-C₁₆ alkyl, for example C₁₂-C₁₄, and M is alkali metal such as lithium, sodium or potassium.

10 Examples of secondary alkyl sulfate surfactants are those which have the sulfate moiety on a "backbone" of the molecule, for example those of formula:



15 wherein m and n are independently 2 or more, the sum of m+n typically being 6 to 20, for example 9 to 15, and M is a water-solubilising cation such as lithium, sodium or potassium.

20 Especially preferred secondary alkyl sulfates are the (2,3) alkyl sulfate surfactants of formulae:




25

for the 2-sulfate and 3-sulfate, respectively. In these formulae x is at least 4, for example 6 to 20, preferably 10 to 16. M is cation, such as an alkali metal, for example lithium, sodium or potassium.

30

Examples of alkoxyated alkyl sulfates are ethoxylated alkyl sulfates of the formula:



35

wherein R is a C₈-C₂₀ alkyl group, preferably C₁₀-C₁₈ such as a C₁₂-C₁₆, n is at least 1, for example from 1 to 20, preferably 1 to 15, especially 1 to 6, and M is a salt-forming cation such as lithium, sodium,

potassium, ammonium, alkylammonium or alkanolammonium. These compounds can provide especially desirable fabric cleaning performance benefits when used in combination with alkyl sulfates.

5

The alkyl sulfates and alkyl ether sulfates will generally be used in the form of mixtures comprising varying alkyl chain lengths and, if present, varying degrees of alkoxylation.


10

Other anionic surfactants which may be employed are salts of fatty acids, for example C_8 - C_{18} fatty acids, especially the sodium, potassium or alkanolammonium salts, and alkyl, for example C_8 - C_{18} , benzene sulfonates.

15

Examples of nonionic surfactants are fatty acid alkoxyates, such as fatty acid ethoxyates, especially those of formula:

20



25

wherein R is a straight or branched C_8 - C_{16} alkyl group, preferably a C_9 - C_{15} , for example C_{10} - C_{14} or C_{12} - C_{14} , alkyl group and n is at least 1, for example from 1 to 16, preferably 2 to 12, more preferably 3 to 10.

30

The alkoxyated fatty alcohol nonionic surfactant will frequently have a hydrophilic-lipophilic balance (HLB) which ranges from 3 to 17, more preferably from 6 to 15, most preferably from 10 to 15.

35

Examples of fatty alcohol ethoxyates are those made from alcohols of 12 to 15 carbon atoms and which contain about 7 moles of ethylene oxide. Such materials are commercially marketed under the trademarks Neodol 25-7 and Neodol 23-6.5 by Shell Chemical Company. Other useful Neodols include Neodol 1-5, an ethoxyated fatty alcohol averaging 11 carbon

atoms in its alkyl chain with about 5 moles of ethylene oxide; Neodol 23-9, an ethoxylated primary C_{12} - C_{13} alcohol having about 9 moles of ethylene oxide; and Neodol 91-10, an ethoxylated C_9 - C_{11} primary alcohol
5 having about 10 moles of ethylene oxide.

Alcohol ethoxylates of this type have also been marketed by Shell Chemical Company under the Dobanol trademark. Dobanol 91-5 is an ethoxylated C_9 - C_{11} fatty
10 alcohol with an average of 5 moles ethylene oxide and Dobanol 25-7 is an ethoxylated C_{12} - C_{15} fatty alcohol with an average of 7 moles of ethylene oxide per mole of fatty alcohol.

15 Other examples of suitable ethoxylated alcohol nonionic surfactants include Tergitol 15-S-7 and Tergitol 15-S-9, both of which are linear secondary alcohol ethoxylates available from Union Carbide Corporation. Tergitol 15-S-7 is a mixed ethoxylated
20 product of a C_{11} - C_{15} linear secondary alkanol with 7 moles of ethylene oxide and Tergitol 15-S-9 is the same but with 9 moles of ethylene oxide.

Other suitable alcohol ethoxylated nonionic
25 surfactants are Neodol 45-11, which is a similar ethylene oxide condensation products of a fatty alcohol having 14-15 carbon atoms and the number of ethylene oxide groups per mole being about 11. Such products are also available from Shell Chemical
30 Company.

Further nonionic surfactants are, for example, C_{10} - C_{18} alkyl polyglycosides, such as C_{12} - C_{16} alkyl polyglycosides, especially the polyglucosides. These
35 are especially useful when high foaming compositions are desired. Further surfactants are polyhydroxy fatty acid amides, such as C_{10} - C_{18} N-(3-methoxypropyl) glycamides and ethylene oxide-propylene oxide block polymers of the Pluronic type.

Examples of cationic surfactants are those of the quaternary ammonium type.

- 5 Examples of amphoteric surfactants are C_{10} - C_{18} amine oxides and the C_{12} - C_{18} betaines and sulfobetaines.

10 The total content of surfactants in a laundry or detergent composition is desirably 60 to 95 wt%, especially 75 to 90 wt%. Desirably an anionic surfactant is present in an amount of 50 to 75 wt%, the nonionic surfactant is present in an amount of 5 to 20 wt%, the cationic surfactant is present in an amount of from 0 to 10 wt% and/or the amphoteric
15 surfactant is present in an amount of from 0 to 10 wt%. The amounts are based on the total solids content of the composition, i.e. excluding the water which is present.

- 20 The compositions, particularly when used as laundry washing or dishwashing compositions, may also comprise enzymes, such as protease, lipase, amylase, and cellulase enzymes. Such enzymes are commercially available and sold, for example, under the registered
25 trade marks Esperase, Alcalase, Savinase, Termanyl, Lipolase and Celluzyme by Nova Nordisk A/S. Desirably the enzymes are present in the composition in an amount of from 0.5 to 3 wt%, especially 1 to 2 wt%.

- 30 The compositions may, if desired, comprise a thickening agent or gelling agent. Suitable thickeners are polyacrylate polymers such as those sold under the trade mark CARBOPOL, or the trade mark ACUSOL by Rohm and Hass Company. Other suitable
35 thickeners are xanthan gums. The thickener, if present, is generally present in an amount of from 0.2 to 4 wt%, especially 0.5 to 2 wt%.

Dishwasher compositions usually comprise a detergency

builder. Suitable builders are alkali metal or ammonium phosphates, polyphosphates, phosphonates, polyphosphonates, carbonates, bicarbonates, borates, polyhydroxysulfonates, polyacetates, carboxylates such as citrates, and polycarboxylates. The builder is desirably present in an amount of up to 90 wt%, preferably 15 to 90 wt%, more preferably 15 to 75 wt%, relative to the total content of the composition. Further details of suitable components are given in, for example, EP-A-694,059, EP-A-518,720 and WO 99/06522.

The compositions can also optionally comprise one or more additional ingredients. These include conventional detergent composition components such as further surfactants, bleaches, bleach enhancing agents, builders, suds boosters or suds suppressors, anti-tarnish and anti-corrosion agents, organic solvents, co-solvents, phase stabilisers, emulsifying agents, preservatives, soil suspending agents, soil release agents, germicides, phosphates such as sodium tripolyphosphate or potassium tripolyphosphate, pH adjusting agents or buffers, non-builder alkalinity sources, chelating agents, clays such as smectite clays, enzyme stabilizers, anti-limescale agents, colourants, dyes, hydrotropes, dye transfer inhibiting agents, brighteners, and perfumes. If used, such optional ingredients will generally constitute no more than 10 wt%, for example from 1 to 6 wt%, the total weight of the compositions.

The builders counteract the effects of calcium, or other ion, water hardness encountered during laundering or bleaching use of the compositions herein. Examples of such materials are citrate, succinate, malonate, carboxymethyl succinate, carboxylate, polycarboxylate and polyacetyl carboxylate salts, for example with alkali metal or alkaline earth metal cations, or the corresponding

free acids. Specific examples are sodium, potassium and lithium salts of oxydisuccinic acid, mellitic acid, benzene polycarboxylic acids, C_{10} - C_{22} fatty acids and citric acid. Other examples are organic
5 phosphonate type sequestering agents such as those sold by Monsanto under the trade mark Dequest and alkylhydroxy phosphonates. Citrate salts and C_{12} - C_{18} fatty acid soaps are preferred.

10 Other suitable builders are polymers and copolymers known to have builder properties. For example, such materials include appropriate polyacrylic acid, polymaleic acid, and polyacrylic/polymaleic and
15 copolymers and their salts, such as those sold by BASF under the trade mark Sokalan.

The builders generally constitute from 0 to 3 wt%, more preferably from 0.1 to 1 wt%, by weight of the compositions.

20 Compositions which comprise an enzyme may optionally contain materials which maintain the stability of the enzyme. Such enzyme stabilizers include, for example, polyols such as propylene glycol, boric acid and
25 borax. Combinations of these enzyme stabilizers may also be employed. If utilized, the enzyme stabilizers generally constitute from 0.1 to 1 wt% of the compositions.

30 The compositions may optionally comprise materials which serve as phase stabilizers and/or co-solvents. Example are C_1 - C_3 alcohols or diols such as methanol, ethanol, propanol and 1,2-propanediol. C_1 - C_3 alkanolamines such as mono-, di- and triethanolamines
35 and mono isopropanolamine can also be used, by themselves or in combination with the alcohols.

The compositions may optionally comprise components which adjust or maintain the pH of the compositions at

optimum levels. Examples of pH adjusting agents are NaOH and citric acid. The pH may be from, for example, 1 to 13, such as 8 to 11 depending on the nature of the composition. For example, a dishwashing composition desirably has a pH of 8 to 11, a laundry composition has a pH of 7 to 9, and a water-softening composition desirably has a pH of 7 to 9.

One or more than one phase may be present. For example the container may be filled with an aqueous composition and a liquid composition which is immiscible with the aqueous composition. It may also be filled with an aqueous composition and a separate solid composition, for example in the form of a ball or pill.

The present invention will now be further explained in the following Examples.

Example 1

A dishwashing composition was prepared by mixing together the following components in the weight proportions indicated:

Potassium tripolyphosphate powder	12%
Sodium tripolyphosphate powder	30%
Isothiazolinone	0.1%
Polyacrylate thickener (Carbopol)	1%
Nonionic surfactant	0.5%
Sodium citrate	10%
Dehardened water	46.4%

A Multivac thermoforming machine operating at 6 cycles/min and at ambient conditions of 25°C and 35% RH ($\pm 5\%$ RH) was used to thermoform a PVOH film. This was Monosol M8534 obtained from Chris Craft Inc, Gary, Indiana, USA, having a degree of hydrolysis of 88% and a thickness of 100 μm . The PVOH film was thermoformed

into a rectangular mould of 39mm length, 29mm width and 16mm depth, with the bottom edges being rounded to a radius of 10mm, at 115-118°C. The thus formed pocket was filled with 10 ml of the dishwashing composition, and a 75 µm thick Monosol M8534 PVOH film was placed on top and heat sealed at 144-148°C. The thus produced containers were separated from each other by cutting the flanges. Each container was initially limp, but attained an attractive, rounded appearance after a few minutes.

Example 2

The following formulations were prepared by mixing together the indicated components in the weight proportions indicated. In all instances the compositions were filled into containers following the procedure described in Example 1, and containers having an attractive, rounded appearance were obtained.

A laundry detergent composition:

	Sodium carbonate	20%
25	Nonylphenol ethoxylate	10%
	Accusol 820 obtainable from	
	Rohm and Haas Company	3.3%
	Sodium citrate	5%
	Dehardened water	61.7%

An automatic dishwasher detergent:

	Sodium citrate	8%
	Van Gel ES thickener obtainable	
35	from R.T.Vanderbilt Company	4%
	Tetrapotassium pyrophosphate	10%
	Sodium tripolyphosphate	30%
	Anhydrous sodium metasilicate	2%
	Sodium xylene sulfonate	2.25%

Deceth-4-phosphate	0.75%
Dehardened water	43%

A heavy duty laundry liquid:

5	Neodol 25-7 C ₁₂₋₁₅ linear alcohol	18%
	Biosoft D-62 sodium	
	alkylbenzenesulfonate	5.5%
	Sodium carbonate	2%
10	Anhydrous sodium metasilicate	5%
	Tetrapotassium pyrophosphate	20%
	Sodium citrate	7.5%
	Carbopol ETDZ691 polymer	
	obtainable from Goodrich	0.5%
15	Dehardened water	41.5%

A slurry-type laundry detergent:

	Sodium carbonate	40%
20	Sodium citrate	4.8%
	Accusol 820 obtainable from	
	Rohm and Haas	2%
	Accusol 810 obtainable from	
	Rohm and Haas	4%
25	Sodium tripolyphosphate	10%
	Accusol 445 obtainable from	
	Rohm and Haas	2%
	Nonylphenol ethoxylate	10%
	Dehardened water	27.2%

30

A dishwashing composition:

	Accusol 810	11%
	Accusol 445N	4%
35	Sodium tripolyphosphate	20%
	Tetrapotassium pyrophosphate	10%
	Potassium silicate	29%
	Triton CF-32 alkylamine	
	ethoxylate	3%

Potassium citrate
Dehardened water

5%
18%

CLAIMS

1. A water-soluble container containing an aqueous
5 composition, wherein:
 - a) the container comprises a thermoformed poly(vinyl alcohol) film; and
 - b) the aqueous composition contains greater than
3 wt% free water, based on the weight of the aqueous
10 composition.
2. A container according to claim 1 wherein the
aqueous composition is a dishwashing, water-softening,
laundry or detergent composition or is a rinse-aid.
15
3. A container according to any one of the preceding
claims which is suitable for use in a domestic washing
machine.
- 20 4. A container according to claim 1 wherein the
aqueous composition is a disinfectant, antibacterial
or antiseptic composition.
- 25 5. A container according to claim 1 wherein the
aqueous composition is a refill composition for a
trigger-type spray.
6. A container according to any one of the preceding
claims wherein the aqueous composition comprises more
30 than 6 wt% free water.
7. A container according to claim 6 wherein the
aqueous composition comprises more than 20 wt% free
water.
35
8. A container according to any one of the preceding
claims which is soluble in water at room temperature
(20°C).

9. A container according to any one of the preceding claims which comprises two poly(vinyl alcohol) films sealed together.
- 5 10. Use of a thermoformed poly(vinyl alcohol) film to package an aqueous composition containing greater than 3 wt% free water, based on the weight of the aqueous composition.
- 10 11. A process for producing a container as defined in any one of claims 1 to 9 which comprises:
- a) thermoforming a first poly(vinyl alcohol) film to produce a pocket;
 - b) filling the pocket with the aqueous
 - 15 composition;
 - c) placing a second poly(vinyl alcohol) film on top of the filled pocket; and
 - d) sealing the first film and second film together.



Application No: GB 0020965.0
Claims searched: 1-11

Examiner: Michael Conlon
Date of search: 2 February 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
 UK Cl (Ed.S): C5D D181 B8C CWP3 CWPT1 CWPT2 A5E ES EX
 Int Cl (Ed.7): B65D 65/46 C11D 17/04 A01N 25/00
 Other: Online: WPI EPODOC PAJ

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB2118961 A (Firmenich) claim 2	1-11
A	EP0347219 A1 (May & Baker) column 5 lines 29-33	1
A	EP0155606 A2 (Schering) page 5 lines 1-3	1
X	WO94/14941 A1 (Berol Nobel) page 2 lines 8-18 Examples 1-4, 7	1-3
X	WO94/04656 A1 (Kao) Table 3 Detergent composition Nos.1-8,10-12	1-3
Y	WO92/17382 A1 (Rhone-Poulenc) Example 2	1, 11
X	US4973416 (Procter & Gamble) Example 1	1-11
X,Y	CA1112534 (Procter & Gamble) the Examples	1-11
A	Derwent Abstract No. 1997-358496 [33] relating to JP090150476 (Aicello) 10.06.1997	1
A	Derwent Abstract No. 1999-163453 [14] relating to JP110021594 (Kao) 26.01.1999	1

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.